

		Out going Inspection Sheet				Make	Check	App
						Dreamus		
Customer		ALT	Model : 4AI20-CMXX03			MP Line : VN LINE		
Q'TY		4,000 PCS	Inspection Date : 2021.11.15			Lot Size : 1st		

Sec	ITEM	Spec	1	2	3	4	5	6	7		
D i m e n s i o n s	Assembly Size	Transverse	69.43±1.0mm	69.30	69.29	69.28	69.27	69.28	69.28	69.27	n=7 c=0
		Length	49.0±1.0mm	48.87	48.85	48.85	48.84	48.85	48.83	48.86	
		Height	35.0±1.0mm	34.33	34.33	34.30	34.30	34.31	34.32	35.32	
	Wire	Color	50.0±5.0mm	53.46	53.47	53.47	53.46	53.46	53.47	53.47	
			Red, Black	OK	OK	OK	OK	OK	OK	OK	
		Housing	White	OK	OK	OK	OK	OK	OK	OK	
F U N C T I O N I N S P E C T I O N	POLARITY		Right : +	OK	OK	OK	OK	OK	OK	OK	
	SPL		136 ± 3 dB at 1W / 15mm	138.18	138.17	138.12	138.27	138.17	138.30	138.26	
	THD		Less than 10% at 1KHz / 1W	OK	OK	OK	OK	OK	OK	OK	
		RESONANCE FREQUENCY (Fo)		IMPEDANCE		TEST CONDITION		DEFECT ITEM		DEFA'TY	
		420 Hz ± 84 Hz		4Ω ± 15%		OPERATION TEST KS A ISO 2859 G- II AQL = 0.25% n = 200 Ac = 1 TEST : 5.65 V					
		(336 Hz ~ 504 Hz)		(3.4 Ω ~ 4.6 Ω)							
		n = 10 c = 0									
	1	432	4.4	APPERARANCE KS A ISO 2859 G- II AQL = 0.40% n = 200 Ac = 2		TOTAL		0			
	2	432	4.5			RESULT		OK NG			
	3	440	4.2								
	4	438	4.1								
	5	440	4.1								
	6	440	4.2								
	7	436	4.4								
	8	435	4.3			TOTAL		0			
9	437	4.2									
10	441	4.1									
AVE	437	4.3			TOTAL		0				
RESULT	OK NG				RESULT		OK NG				

RoHS Compliance

(주) 해당없는 검사항목 사선으로 삭제한다.

REMARKS	RESULT	STAMP
	PASS 2021.11.15 O.Q.C	4AI20- CMXX03 4Ω 8W LOT NO MARKING 4AI20- CMXX03 4Ω 8W 174,1X1



