

SPECIFICATIONS

(Draft Version)

* Model Identifications

Model Code	Customer P/ N
4AI20-CMXX03	

Signed for/on behalf of us. By: R&D manager Mr. ----- Date: . .	Signed for/on behalf of you. By: ----- Date : . .
--	--

This Specifications will be valid after the date of acceptance by both 'Dreamus' and the customer. Without formal request for updating by one of the involved parties, this Specifications will be valid until the end of usage of the relevant products by the customer.




1. REVISION RECORD


Rev. No	DATE	DESCRIPTION	By	Chk.	App.
0	13. APR. 2021	R&D and ECO Release			
1					
2					
3					
4					
5					
6					
7					
8					

2. RoHS ENVIRONMENTAL STANDARDS


CLASSIFICATIONS	SUBSTANCES	COMPLIANCE	
		YES	NO
RoHS	Lead and its Compounds	☒	☐
	Cadmium and its Compounds	☒	☐
	Mercury and its Compounds	☒	☐
	Hexavalent Chromium and its Compounds	☒	☐
	Polybrominated Biphenyls	☒	☐
	Polybrominated Diphenylethers	☒	☐

DESIGNED		CHECKED		APPROVED	
13. APR. 2021		13. APR. 2021		13. APR. 2021	


3-1. MECHANICAL CHARACTERISTICS (Unit Only)




UNIT : mm
TOLERANCE : ± 1.0

DESIGNED		CHECKED		APPROVED	
13. APR. 2021		13. APR. 2021		13. APR. 2021	

3-2. MECHANICAL CHARACTERISTICS (Assy)



UNIT : mm
TOLERANCE : ±1.0

DESIGNED		CHECKED		APPROVED	
13. APR. 2021		13. APR. 2021		13. APR. 2021	

4. ELECTRICAL CHARACTERISTICS (Unit Only)


PARAMETER	SPECIFICATION	UNIT
Impedance AT 700Hz / 1.0Vrms	4 ± 0.6	Ω
Power Rating (Nor / Max)	8 / 15	Watt
Polarity	When a positive DC current is applied to the marked (+), diaphragm shall move forward.	

5. ACOUSTIC CHARACTERISTICS (Unit Only)

PARAMETER	SPECIFICATION	UNIT
Sound Pressure Level At 1.0W Input & 1.0m distance	80 ± 3 Avg (0.3, 0.6, 1.0, 1.2) kHz	dB
Total Harmonic Distortion	Less than 5% at 1KHz, 1W	%
Resonance Frequency (Fo) At 1.0 Vrms	180 ± 36	Hz
Frequency Range	Fo ~ 20	KHz
Buzz and Rattle etc.	Should not be audible at 8W (RMS. 5.65V) sine wave from Fo to 20 KHz.	


6. ENVIRONMENTAL CHARACTERISTICS (Unit Only)

PARAMETER	SPECIFICATION	UNIT
Operating Temperature Range	-20 ~ 65	°C
Storage Temperature Range	-25 ~ 70	°C

DESIGNED		CHECKED		APPROVED	
13. APR. 2021		13. APR. 2021		13. APR. 2021	



7. MEASUREMENT STANDARD

7-1 Measurement Environment




7-2 Measurement Environment

①	Baffle Box	JIS C 5532
②	Speaker Unit	4AI20-CMXX03
③	Microphone	CLIO MIC-02
④	Analyzer	CLIO FW V.12
⑤	Amplifier	MARLOSA SA-30.PSD
⑥	Anechoic room	2.5×2.5×3 (m)
⑦	Input Power	1.0 (W)
⑧	Testing Distance	1.0 (M)
⑨	Test Mode	TIME SELECTIVE RESPONSE (TSR)


DESIGNED		CHECKED		APPROVED	
13. APR. 2021		13. APR. 2021		13. APR. 2021	

8. TYPICAL FREQUENCY RESPONSE CURVE (Unit Only)



NOTE:

- The frequency response curve is drawn with the "1/3OCT" smoothing Function of CLIO 12.

DESIGNED		CHECKED		APPROVED	
13. APR. 2021		13. APR. 2021		13. APR. 2021	

9. RELIABLE TEST STANDARDS

No	Test Item	Conditions
9-1	After Test	Sensitivity difference shall be within $\pm 3\text{dB}$ after test.
9-2	High Temperature Test	High temperature.....+ 70°C Duration.....96 hours
9-3	Low Temperature Test	Low temperature..... - 25°C Duration.....96 hours
9-4	Thermal Shock Test	Temperature - 25°C $\leftrightarrow$ + 70°C Duration.....2hours Cycle.....15 cycles
9-5	Humidity Test	Temperature.....+ 40°C Relative humidity.....90% Duration.....96 hours
9-6	Vibration Test	Vibration.....10 - 55Hz / min Amplitude.....1.5mm Duration..... 2 hour in each of 3axes
9-7	Drop Test	Height.....1.5 M Cycle.....1 cycles
9-8	Load Test	Subject samples to White Noise for 96 hours at 8W input power

DESIGNED
CHECKED
APPROVED

13. APR. 2021



13. APR. 2021



13. APR. 2021

