

SMD ■ B

19-137/R6GHBHC/S1906/2T



Features

- . Package in 8mm tape on 7" diameter reel.
- . Compatible with automatic placement equipment.
- . Compatible with infrared and vapor phase reflow solder process.
- . Multi-color type.
- . Pb-free.
- . ESD protection
- . The product itself will remain within RoHS compliant version.
- . Compliance with EU REACH.
- . Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm).

Description

- . The 19-137 SMD LED is much smaller than lead frame type components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained.
- . Besides, lightweight makes them ideal for miniature applications. etc.

Applications

- . Backlighting in dashboard and switch.
- . Telecommunication: indicator and backlighting in telephone and fax.
- . Flat backlight for LCD, switch and symbol.
- . General use.

Device Selection Guide

Code	Chip Materials	Emitted Color	Resin Color
R6	AlGaInP	Brilliant Red	Water Clear
GH	InGaN	Brilliant Green	
BH	InGaN	Blue	

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Code	Rating	Unit
Reverse Voltage	V _R		5	V
Forward Current	I _F		25	mA
Peak Forward Current (Duty 1/10 @1KHz)	I _{FP}	R6	60	mA
		GH	100	
		BH	100	
Power Dissipation	P _d	R6	60	mW
		GH	95	
		BH	95	
Electrostatic Discharge(HBM)	ESD		2000	V
Operating Temperature	T _{opr}		-40 ~ +85	℃
Storage Temperature	T _{stg}		-40 ~ +90	℃
Soldering Temperature	T _{sol}		Reflow Soldering : 260 ℃ for 10 sec. Hand Soldering : 350 ℃ for 3 sec.	

Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Code	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I _v	R	28.5	-----	72.0	mcd	R6 : IF=7mA
		G	112.0	-----	285.0	mcd	GH : IF=7mA
		B	14.5	-----	36.0	mcd	BH : IF=5mA
		Mix*	180.0	-----	360.0	mcd	
Viewing Angle	2θ _{1/2}		100	120	140	Deg	
Peak Wavelength	λ _p	R6	-----	632		nm	
		GH	-----	518			
		BH	-----	468			
Dominant Wavelength	λ _d	R6	616	-----	632	nm	R6 : IF=7mA
		GH	515	-----	535		GH : IF=7mA
		BH	460	-----	475		BH : IF=5mA
Forward Voltage	V _F	R6	1.6	-----	2.2	V	
		GH	2.5	-----	3.3		
		BH	2.4	-----	3.2		
Reverse Current	I _R		-----	-----	10	μA	V _R =5V

*When three LED dies are operated simultaneously.

Note:

1. Tolerance of Luminous Intensity: ±11%
2. Tolerance of Forward Voltage: ±0.10V
3. Tolerance of Dominant Wavelength ±1nm
3. RA test @ 5mA.

Bin Range of Luminous Intensity

Bin Code	Min.	Max.	Unit	Condition
S1	180.0	225.0	mcd	R6 : IF=7.0mA
S2	225.0	285.0		GH : IF=7.0mA
T1	285.0	360.0		BH : IF=5.0mA

R6

Bin Code	Min.	Max.	Unit	Condition
N	28.5	45.0	mcd	IF=7.0mA
P	45.0	72.0		

GH

Bin Code	Min.	Max.	Unit	Condition
R	112.0	180.0	mcd	IF=7.0mA
S	180.0	285.0		

BH

Bin Code	Min.	Max.	Unit	Condition
LA	14.5	22.5	mcd	IF=5.0mA
MA	22.5	36.0		

Bin Range Of Dom. Wavelength

R6

Bin Code	Min.	Max.	Unit	Condition
1	616	632	nm	IF=7.0mA

GH

Bin Code	Min.	Max.	Unit	Condition
1	515	535	nm	IF=7.0mA

BH

Bin Code	Min.	Max.	Unit	Condition
1	460	475	nm	IF=5.0mA

Note:

1. Tolerance of Luminous Intensity: $\pm 11\%$
2. Tolerance of Dominant Wavelength $\pm 1\text{nm}$

Chromaticity Coordinates Specifications for Bin Grading

Bin Code	CIE_x	CIE_y	Condition
220	0.207	0.250	R6 : IF=7.0mA GH : IF=7.0mA BH : IF=5.0mA
	0.207	0.275	
	0.232	0.285	
	0.232	0.260	
221	0.232	0.260	
	0.232	0.285	
	0.257	0.295	
	0.257	0.27	
PW 05	0.257	0.270	
	0.257	0.295	
	0.282	0.305	
	0.282	0.280	
PW 06	0.282	0.280	
	0.282	0.305	
	0.307	0.315	
	0.307	0.290	
238	0.207	0.275	
	0.207	0.300	
	0.232	0.310	
	0.232	0.285	
239	0.232	0.285	
	0.232	0.310	
	0.257	0.320	
	0.257	0.295	
PW09	0.257	0.295	
	0.257	0.320	
	0.282	0.330	
	0.282	0.305	
PW 10	0.282	0.305	
	0.282	0.330	
	0.307	0.340	
	0.307	0.315	

*When three LED dies are operated simultaneously.

Notes:

1.The C.I.E. 1931 chromaticity diagram (Tolerance ± 0.01).

2.The products are sensitive to static electricity and care must be fully taken when handling products.

Bin Code	CIE_x	CIE_y	Condition
256	0.207	0.300	R6 : IF=7.0mA GH : IF=7.0mA BH : IF=5.0mA
	0.207	0.325	
	0.232	0.335	
	0.232	0.310	
257	0.232	0.310	
	0.232	0.335	
	0.257	0.345	
	0.257	0.320	
PW13	0.257	0.320	
	0.257	0.345	
	0.282	0.355	
	0.282	0.330	
PW14	0.282	0.330	
	0.282	0.355	
	0.307	0.365	
	0.307	0.340	
274	0.207	0.325	
	0.207	0.350	
	0.232	0.360	
	0.232	0.335	
275	0.232	0.335	
	0.232	0.360	
	0.257	0.370	
	0.257	0.345	
276	0.257	0.345	
	0.257	0.370	
	0.282	0.380	
	0.282	0.355	
277	0.282	0.355	
	0.282	0.380	
	0.307	0.390	
	0.307	0.365	


*When three LED dies are operated simultaneously.

Notes:

1.The C.I.E. 1931 chromaticity diagram (Tolerance ± 0.01).

2.The products are sensitive to static electricity and care must be fully taken when handling products.

CIE Chromaticity Diagram









Notes:

- 1.The C.I.E. 1931 chromaticity diagram (Tolerance ± 0.01).
- 2.The products are sensitive to static electricity and care must be fully taken when handling products.







Typical Electro-Optical Characteristics Curves

R6









Typical Electro-Optical Characteristics Curves

GH





Typical Electro-Optical Characteristics Curves


BH




Package Dimension



Polarity




Side



Bottom

Recommend soldering pad




Suggested pad dimension is just for reference only.
Please modify the pad dimension based on individual need.

Note: Tolerances unless mentioned ± 0.1 mm. Unit = mm


Moisture Resistant Packing Materials

Label Explanation




- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Chromaticity Coordinates & Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number

Reel Dimensions




Note: The tolerances unless mentioned is $\pm 0.1\text{mm}$,Unit = mm

Carrier Tape Dimensions: Loaded quantity 2000 PCS per reel



Note: The tolerances unless mentioned is $\pm 0.1\text{mm}$, Unit = mm

Moisture Resistant Packaging



Precautions For Use

1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen).

2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 Before opening the package: The LEDs should be kept at 30°C or less and 90%RH or less.

2.3 After opening the package: The LED's floor life is 1 year under 30°C or less and 60% RH or less.


If unused LEDs remain, it should be stored in moisture proof packages.

2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment : 60±5°C for 24 hours.

3. Soldering Condition

3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.


3.4 After soldering, do not warp the circuit board.

4. Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 350°C for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

5. Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



Application Restrictions

High reliability applications such as military/aerospace, automotive safety/security systems, and medical equipment may require different product. If you have any concerns, please contact Everlight before using this product in your application. This specification guarantees the quality and performance of the product as an individual component. Do not use this product beyond the specification described in this document.

DISCLAIMER

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.
2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.
3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.
6. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.