

Test Report

Common Information

Test Model Name:

Test Mode:

Manufacturer:

Tester:

Hardware Setup: EMI conducted\Voltage with ENV216_FO(101235) - [EMI conducted]

Subrange 1


Frequency Range: 150 kHz - 30 MHz

Receiver: ESCI 3 [ESCI 3]
@ GPIB0 (ADR 20), SN 100032/003, FW 4.42

Signal Path: ESCI 3-ENV216 FO(101235)
FW 1.0

LISN: Correction Table: 3CE Cable Loss
ENV216 FO(101235)
Correction Table (Line 0): ENV216_FO_N(101235)
Correction Table (Line 1): ENV216_FO_L1(101235)

3CE_Class B_L1



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.154500	55.3	3000.0	9.000	On	L1	9.9	10.5	65.8
0.280500	52.9	3000.0	9.000	On	L1	9.8	7.9	60.8
0.316500	51.7	3000.0	9.000	On	L1	9.9	8.1	59.8
0.411000	45.6	3000.0	9.000	On	L1	10.0	12.0	57.6

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.303000	40.4	3000.0	9.000	On	L1	9.8	9.8	50.2
0.406500	39.5	3000.0	9.000	On	L1	10.0	8.2	47.7
0.618000	33.5	3000.0	9.000	On	L1	10.0	12.5	46.0
1.356000	33.6	3000.0	9.000	On	L1	9.9	12.4	46.0