



International Certification Corp. (全球檢測股份有限公司)

Tel : 886-3-271-8666

Fax : 886-3-318-0155

No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)

IEC/EN 61000-4-2 ESD TEST RECORD

Applicant:	鴻齡	ICC No:	220414P02
EUT:	SWAN	Model:	BFX-UA300
Test mode:		Sample No:	E01
Operating Conditions of EUT: LAN1Gbps ping test,HDMI out,AUX+MIC+USB3.0+USB2.0(load)+BT(遙控器)			
Input Voltage:	AC 230 V / 50 Hz or DC V	Approved by	

Test Equipment: ☒ EMTest Dito ☐ _____						Test Site: ES01-WS					
Temperature / Humidity: 22 °C / 48 % Atmospheric Pressure: 101 kPa (86kPa to 106kPa)											
Tested by: Sheon Tu						Date: 2022 (yy) 04 (mm) 21 (dd)					
☐ IEC 61000-4-2 ☒ EN 61000-4-2 ☐ EN 55024 ☐ EN 301489 ☐ KCC						☐ IEC 61000-4-2 ☐ EN 61000-4-2 ☐ EN 55024 ☐ EN 301489 ☐ _____					
Direct Application						Direct Application					
Test Voltage (kV)	Polarity	Test Point	Contact Discharge	Air Discharge	Performance Criteria	Test Voltage (kV)	Polarity	Test Point	Contact Discharge	Air Discharge	Performance Criteria
2,4,8	+/-	1~12	N/A	Note1	A						
2,4	+/-	13	Note1	N/A	A						
2	+/-	14	Note1	N/A	A						
4	+/-	14	Note2	N/A	B						
Indirect Application						Indirect Application					
Test Voltage (kV)	Polarity	Test Point	Horizontal Coupling Plane (HCP)	Vertical Coupling Plane (VCP)	Performance Criteria	Test Voltage (kV)	Polarity	Test Point	Horizontal Coupling Plane (HCP)	Vertical Coupling Plane (VCP)	Performance Criteria
2,4	+/-	At front, rear, left and right side	Note1	Note1	A						
☒ EN 61000-4-2 Performance Criterion: B						☐ _____ Performance Criterion: _____					

N/A means not applicable.

Please See attached page for a description of the test points.

Test Result :

Note1 : There was no abnormal situation during the test compared with initial operation.

Note2 : The EUT had "reset" situation happened during the test, but could be self-recoverable after the test.

According to : ☐ Standard ; ☒ Manufacturer