



International Certification Corp. (全球檢測股份有限公司)

Tel : 886-3-271-8666

Fax : 886-3-318-0155

No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)

IEC/EN 61000-4-11 DIP TEST RECORD

Applicant:	鴻齡	ICC No:	
EUT:		Model:	SBB OTT
Test mode:	Model1 , 2	Sample No:	
Operating Conditions of EUT:	Mode1:IR remote control ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording Mode2: BT remote control with earphone ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording		
Input Voltage:	AC 220 V / 60 Hz or DC__V	Approved by	

Test Site:EX01-WS													
Temperature / Humidity: 19 °C / 58% Atmospheric Pressure: 103 kPa (86kPa to 106kPa)													
Tested by: JN Chen										Date: 2019 (yy) 03 (mm) 06 (dd)			
Model1 , 2													
☒ IEC 61000-4-11 ☐ EN 61000-4-11 ☐ EN 55024 ☐ EN 301489 ☒ KCC							☐ IEC 61000-4-11 ☐ EN 61000-4-11 ☐ EN 55024 ☐ EN 301489 ☐						
Test Voltage	Item	Reduction	Residual	Voltage Cycle	Observation	Performance Criteria	Test Voltage	Item	Reduction	Residual	Voltage Cycle	Observation	Performance Criteria
		Voltage (%)							Voltage (%)				
220V/60Hz	Voltage Dip	>95		0.5	Note 1	A							
220V/60Hz	Voltage Dip	30		30	Note 1	A							
220V/60Hz	Voltage Interruption	>95		300	Note 2	C							
100V/60Hz	Voltage Dip	>95		0.5	Note 1	A							
100V/60Hz	Voltage Dip	30		30	Note 1	A							
100V/60Hz	Voltage Interruption	>95		300	Note 2	C							
☒ KCC Performance Criterion: C							☐ Performance Criterion:						
Test Result : Note1 : There was no abnormal situation during the test compared with initial operation. Note2 : The EUT lost power during the test and must be recovered manually.													
According to : ☒ Standard ; ☐ Manufacturer													