



International Certification Corp. (全球檢測股份有限公司)

Tel : 886-3-271-8666

Fax : 886-3-318-0155

No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)

IEC/EN 61000-4-5 SURGE TEST RECORD

Applicant:	鴻齡	ICC No:	
EUT:		Model:	SBB OTT
Test mode:	Mode1 , 2	Sample No:	
Operating Conditions of EUT:	Mode1: IR remote control ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording Mode2: BT remote control with earphone ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording		
Input Voltage:	AC 220 V / 60 Hz or DC ___ V	Approved by	

Test Equipment: ☒ TESEQ ☐ _____						Test Site: SE01-WS					
Repetition rate : ☒ 60 sec ☐ _____ sec											
Number of test: ☒ 5 time/each ☐ _____ time/each											
Temperature / Humidity: 20 °C / 58 % Atmospheric Pressure: 101 kPa (86kPa to 106kPa)											
Tested by: JN Chen						Date: 2019(yy) 03 (mm) 07 (dd)					
Mode1 , 2											
☒ IEC 61000-4-5 ☐ EN 61000-4-5 ☐ EN 55024 ☐ EN 301489 ☒ KCC						☐ IEC 61000-4-5 ☐ EN 61000-4-5 ☐ EN 55024 ☐ EN 301489 ☐ _____					
Test Port	Polarity	Test Voltage (kV)	Phase Angle	Observation	Performance Criteria	Test Port	Polarity	Test Voltage (kV)	Phase Angle	Observation	Performance Criteria
For power ports ☒ 1.2/50µs(8/20µs)						For power ports ☐ 1.2/50µs(8/20µs)					
L1-L2	+/-	0.5,1	0°/90°/180°/270°	Note	A						
For telecom & signal ports ☒ 1.2/50µs(8/20µs) ☐ 10/700µs						For telecom & signal ports ☐ 1.2/50µs(8/20µs) ☐ 10/700µs					
LAN	+/-	0.5	-	Note	A						
☒ KCC Performance Criterion: A						☐ _____ Performance Criterion: _____					
Test Result :											
Note : There was no abnormal situation during the test compared with initial operation. _____											
According to : ☐ Standard ; ☒ Manufacturer											