



International Certification Corp. (全球檢測股份有限公司)

Tel : 886-3-271-8666

Fax : 886-3-318-0155

No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)

IEC/EN 61000-4-2 ESD TEST RECORD

Applicant:	鴻齡	ICC No:	
EUT:		Model:	SBB OTT
Test mode:	Mode1 , 2	Sample No:	
Operating Conditions of EUT:	Mode1:IR remote control ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording Mode2: BT remote control with earphone ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording		
Input Voltage:	AC 230 V / 50 Hz or DC__V	Approved by	

Test Equipment: ☒ EMTest Dito ☐ _____						Test Site:ES01-WS					
Temperature / Humidity: 19 °C / 48 % Atmospheric Pressure: 103 kPa (86kPa to 106kPa)											
Tested by: JN Chen						Date: 2019 (yy) 03 (mm) 11 (dd)					
Mode1						Mode2					
☒ IEC 61000-4-2 ☐ EN 61000-4-2 ☒ EN 55024 ☐ EN 301489 ☐ _____						☒ IEC 61000-4-2 ☐ EN 61000-4-2 ☒ EN 55024 ☐ EN 301489 ☐ _____					
Direct Application						Direct Application					
Test Voltage (kV)	Polarity	Test Point	Contact Discharge	Air Discharge	Performance Criteria	Test Voltage (kV)	Polarity	Test Point	Contact Discharge	Air Discharge	Performance Criteria
2,4,8	+/-	1~13	N/A	Note1	A	2,4,8	+/-	1~11	N/A	Note1	A
2,4	+/-	14	Note1	N/A	A	2,4	+/-	1~11	N/A	Note1	A
-						8	+/-	12,13	N/A	Note2	B
						2,4	+/-	14	Note1	N/A	A
						-					
Indirect Application						Indirect Application					
Test Voltage (kV)	Polarity	Test Point	Horizontal Coupling Plane (HCP)	Vertical Coupling Plane (VCP)	Performance Criteria	Test Voltage (kV)	Polarity	Test Point	Horizontal Coupling Plane (HCP)	Vertical Coupling Plane (VCP)	Performance Criteria
2, 4	+/-	At front, rear, left and right side	Note1	Note1	A	2, 4	+/-	At front, rear, left and right side	Note1	Note1	A
☒ EN 55024 Performance Criterion: A						☒ EN 55024 Performance Criterion: B					

N/A means not applicable.

Please See attached page for a description of the test points.

Test Result :

Note 1: There was no abnormal situation during the test compared with initial operation.

Note 2: The EUT Voice Output from HDMI Monitor Speaker during the test, but could be self-recoverable from remote control's earphone Output Voice after the test.

According to : ☒ Standard ; ☐ Manufacturer