



International Certification Corp. (全球檢測股份有限公司)

Tel : 886-3-271-8666

Fax : 886-3-318-0155

No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)

IEC/EN 61000-4-3 RS TEST RECORD

Applicant:	鴻齡	ICC No:	
EUT:		Model:	SBB OTT
Test mode:	Mode1 , 2	Sample No:	
Operating Conditions of EUT:		Mode1:IR remote control ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording Mode2: BT remote control with earphone ,Run LAN Ping test , Play VLC MP4 , “ADB” test program recording	
Input Voltage:	AC <u>230</u> V / <u>50</u> Hz or DC <u> </u> V	Approved by	

Frequency step size : <u>1</u> % Dwell time : <u>3</u> s Test Site: <u>RS01-WS</u>											
Modulation: ☒ AM 1kHz 80% ☐ AM <u> </u> Hz <u> </u> % ☐ Pulse <u> </u> Hz ☐ <u> </u>											
Temperature / Humidity: <u>20</u> °C / <u>60</u> % Atmospheric Pressure: <u>103</u> kPa (86kPa to 106kPa)											
Tested by: <u>JN Chen</u>						Date: <u>2019</u> (yy) <u>03</u> (mm) <u>06</u> (dd)					
Mode 1 , 2											
☒ IEC 61000-4-3 ☐ EN 61000-4-3 ☒ EN 55024 ☐ EN 301489 ☐ <u> </u>						☐ IEC 61000-4-3 ☐ EN 61000-4-3 ☐ EN 55024 ☐ EN 301489 ☐ <u> </u>					
Frequency Range (MHz)	Azimuth	Polarity	Test Field Strength (V/m)	Observation	Performance Criteria	Frequency Range (MHz)	Azimuth	Polarity	Test Field Strength (V/m)	Observation	Performance Criteria
80 – 1000	0	V&H	3	Note	A						
80 – 1000	90	V&H	3	Note	A						
80 – 1000	180	V&H	3	Note	A						
80 – 1000	270	V&H	3	Note	A						
-											
☒ <u>EN 55024</u> Performance Criterion: <u>A</u>						☐ <u> </u> Performance Criterion: <u> </u>					
Test Result :											
Note : <u>There was no abnormal situation during the test compared with initial operation.</u>											
According to : ☒ Standard ; ☐ Manufacturer											