

Measurement Name	Minimum	Maximum	Mean	pk-pk	Standard Deviation	RMS	Population	Status
Eye Diagram Test	-	-	-	-	-	-	-	Pass
Signal Rate	11.92653Mbps	12.07321Mbps	11.99729Mbps	0.0000bps	45.41757kbps	11.99512Mbps	29	Pass
Crossover Voltage	1.534376 V	1.745834 V	1.669772 V	211.4584mV	54.16268mV	1.670606 V	20	Pass
EOP Width	-	-	166.3331ns	-	-	-	1	Pass
Consecutive Jitter	-372.1563ps	374.9701ps	19.98416ps	747.1264ps	260.9352ps	254.3696ps	18	Pass
Paired JK Jitter	-192.4138ps	362.0690ps	32.64368ps	554.4828ps	175.8193ps	167.6723ps	8	Pass
Paired KJ Jitter	-372.1563ps	211.0345ps	8.534355ps	583.1908ps	168.6240ps	159.2092ps	9	Pass

Additional Information :

Rising Edge Rate:266.8343 V/us (Equivalent Rise Time = 9.8938 ns)

Falling Edge Rate:261.7341 V/us (Equivalent Fall Time = 10.087 ns)

* The Overall Result for this test is **Pass**, because individual status of the measurements is **Pass** and it is performed on Tier 6 (as per USB-IF).



TDSUSB2 software version: 4.0.0.2